



LEGEND

- 🚧 Flagger
- ⬇️ Temporary Traffic Signal
- 🚦 Traffic Sign
- 42" Channelizer
- ▨ Work Area
- ➡️ Direction of Traffic
- ||| Portable Rumble Strip Panel

SPEED LIMIT (mph)*	ADT	A	H
50 or greater	up to 2,500	500'	2.5 mi.
	2,500 - 5,000	500'	2.0 mi.
	more than 5,000	1000'	1.5 mi.

* Speed Limit refers to regulatory speed limit before road work.

No detection area required.

Timing for Push-button Actuated Signals

Initial Green = 15 sec.

Green Ext. = 2.5 sec.

Yellow = 4.0 sec.

Install push-button actuated traffic signals.

Program signals to rest in RED.

GREEN and GREEN EXTENSION only are initiated by flagger.

① For Temporary Traffic Signals, meet the requirements of Section 2528.03 of the Standard Specifications except for the following:
In lieu of a trailer or span-wire mounted system, signal heads may be located on the shoulders, one on each side of the roadway. Mount shoulder signal heads a minimum of 8 feet from the bottom of the signal head to the top of the ground surface.

② Locate signal heads 70 to 100 feet beyond "STOP HERE ON RED" sign. Adjust location of signal heads as field conditions warrant.

③ For traffic control zones lasting more than 2 hours, place temporary Portable Rumble Strip Panel.

Possible Contract Items:

- Flagger
- Pilot Car
- Temporary Traffic Signal
- Traffic Control

Possible Tabulations:

- 108-27
- 108-28

 STANDARD ROAD PLAN	REVISION	
	7	4-18-23
TC-218		
SHEET 1 of 1		
REVISIONS: Added speed limit note. Formatted speed limit table.		
 APPROVED BY DESIGN METHODS ENGINEER		
LANE CLOSURE WITH PILOT CAR AND FLAGGER OPERATED SIGNALS		